

type	Staaftafstand aL aQ [mm]	diameter staven		lengte breedte [m]	stekkeinden		Gewicht [kg]	Aantal per pak
		binnen ds1 ds3 [mm]	rand ds2 ds4 [mm]		begin U1 U3 links [mm]	eind U2 U4 rechts [mm]		
QS 196	100.0	5.0	0.0	3.00	50.0	50.0	18.50	50
	100.0	5.0	0.0	2.00	50.0	50.0		
QS 283	100.0	6.0	0.0	3.00	50.0	50.0	26.60	50
	100.0	6.0	0.0	2.00	50.0	50.0		
QS 503	100.0	8.0	0.0	3.00	50.0	50.0	47.40	30
	100.0	8.0	0.0	2.00	50.0	50.0		
QS 130	150.0	5.0	0.0	3.00	75.0	75.0	12.60	50
	150.0	5.0	0.0	2.00	25.0	25.0		
QS 188	150.0	6.0	0.0	3.00	75.0	75.0	18.20	50
	150.0	6.0	0.0	2.00	25.0	25.0		
QS 335	150.0	8.0	0.0	3.00	75.0	75.0	32.40	30
	150.0	8.0	0.0	2.00	25.0	25.0		
Q 130	150.0	5.0	0.0	6.00	75.0	75.0	29.00	50
	150.0	5.0	0.0	2.30	25.0	25.0		
Q 188	150.0	6.0	0.0	6.00	75.0	75.0	41.70	50
	150.0	6.0	0.0	2.30	25.0	25.0		
Q 257	150.0	7.0	0.0	6.00	75.0	75.0	56.80	40
	150.0	7.0	0.0	2.30	25.0	25.0		
Q 335	150.0	8.0	0.0	6.00	75.0	75.0	74.30	30
	150.0	8.0	0.0	2.30	25.0	25.0		
Q 196	100.0	5.0	0.0	6.00	50.0	50.0	42.50	50
	100.0	5.0	0.0	2.30	50.0	50.0		
Q 283	100.0	6.0	0.0	6.00	50.0	50.0	61.30	30
	100.0	6.0	0.0	2.30	50.0	50.0		
B 196 N	100.0	5.0	0.0	6.00	25.0	375.0	40.50	50
	100.0	5.0	0.0	2.40	375.0	25.0		
B 283 N	100.0	6.0	0.0	6.00	25.0	375.0	58.30	30
	100.0	6.0	0.0	2.40	375.0	25.0		
B 385 N	100.0	7.0	0.0	6.00	25.0	375.0	79.40	20
	100.0	7.0	0.0	2.40	375.0	25.0		
B 503 N	100.0	8.0	0.0	6.00	25.0	475.0	100.50	20
	100.0	8.0	0.0	2.40	475.0	25.0		
B 188 N	150.0	6.0	0.0	5.95	25.0	375.0	38.30	50
	150.0	6.0	0.0	2.35	375.0	25.0		
B 257 N	150.0	7.0	0.0	5.95	25.0	375.0	52.10	40
	150.0	7.0	0.0	2.35	375.0	25.0		
B 335 N	150.0	8.0	0.0	5.95	25.0	525.0	64.90	30
	150.0	8.0	0.0	2.35	525.0	25.0		
B 424 N	150.0	9.0	0.0	5.95	25.0	525.0	82.00	20
	150.0	9.0	0.0	2.35	525.0	25.0		
B 524 N	150.0	10.0	0.0	5.95	25.0	525.0	101.40	20
	150.0	10.0	0.0	2.35	525.0	25.0		